

F0330 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 330 litres
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -20°C up to $+55^{\circ}\text{C}$ (with reduced specifications)
- Refrigeration system includes BD series 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system.
- Versions with automatic cooling / heating operation are available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). They maintain consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP.
- AC/DC power supplies (input voltage 100-240Vac 50-60 Hz) available as accessories.

Available versions:

- NDN down to $+0^{\circ}\text{C}$
- NDH from $+30^{\circ}\text{C}$ to $+0^{\circ}\text{C}$
- FDN down to -21°C
- FDH from $+30^{\circ}\text{C}$ to -21°C
- XFDN down to -30°C



easy cooling, smart moving

www.coldtainer.com

F0330 PRODUCT INFO

Model name	F0330/NDN	F0330/NDH	F0330/FDN	F0330/FDH	F0330/XFDN
EE article nr.	816008/00	816008/02	816008/01	816008/03	816008/04
Gross capacity (lt)	330	330	330	330	330
Temperature range (°C)	> +0°C	+30°C to +0°C	> -21°C	+30°C to -21°C	> -30°C
Automatic cooling/heating	no	yes	no	yes	no
Voltage	12-24Vdc	12-24Vdc	12-24Vdc	12-24Vdc	12Vdc
Peak Amps (@12Vdc)	10	10	18	18	25
Fuse on DC cord	30A	30A	30A	30A	50A
External dimensions (mm)	1000 x 1020 x 910	1000 x 1020 x 910	1000 x 1020 x 910	1000 x 1020 x 910	1000 x 1020 x 910
Weight (kg)	80	83	83	86	90
PU insulation (mm)	100	100	100	100	100
"K" insulation factor	0,27 W/m ² K	0,27 W/m ² K	0,27 W/m ² K	0,27 W/m ² K	0,27 W/m ² K
Compressor (model)	BD50F	BD50F	BD80F	BD80F	BD220CL
Refrigerant gas (type)	R134a	R134a	R134a	R134a	R404A
Refrigerant gas (gr)	96	96	130	130	250
Cut-out / cut-in voltage	9,6Vdc-10,9Vdc	9,6Vdc-10,9Vdc	9,6Vdc-10,9Vdc	9,6Vdc-10,9Vdc	11Vdc-12,3Vdc
AC/DC power supply (opt)	560019/00	560019/00	560020/00	560020/00	560020/00
AC/DC power supply input	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz

*with ambient temperature +30°C

